

The Windows-based STINGA product family covers a wide range of stand-alone protocol analyser and simulator products. Both notebook- and desktop-based solutions are available. Protocol stacks like SS7oTDM (E1/T1/J1), SS7oIP, SIP, SIP-T, SIGTRAN, BICC, V5.1/V5.2, ISDN PRA, ISDN BRA, DPNSS/DASS2, Megaco/H.248, MGCP and PNNI are supported.

The STINGA V5 Monitor product is a protocol analyser for real-time V5.1/V5.2 monitoring and decoding over E1.

This product is suitable for V5.1/V5.2 protocol analysis, error tracking, network surveillance, network maintenance and more.



FEATURES

- V5.1/V5.2 monitoring over E1
- Real-time monitoring and decoding
- Multiple E1 line interfaces supported
- Simultaneous monitoring of multiple timeslots
- Filter and search functionality
- Voice monitoring (PC speakers)
- DTMF detector
- Hex decoder
- E1/T1/J1 PCMCIA and PCI cards available
- Running on Windows Vista/XP/2003 Server/2000

SPECIFICATIONS

- E1 interfaces
- E1 alarm signals and link status
- V5-Protection
- V5-Link Control
- V5-Control
- V5-BCC
- V5-PSTN
- LAPV5-EF
- LAPV5-DL
- LAPD
- ISDN PRA
- ISDN BRA

SOFTWARE & HARDWARE

20526: STINGA V5 Monitor

20135: PIST-2MP-PRO PCMCIA, 2xE1/T1/J1

20430: PIST-2MI+ PCI, 2xE1/T1/J1

20440: PIST-4MI+ PCI, 4xE1/T1/J1

20125: PIST-8MI+ PCI, 8xE1/T1/J1

20127: PIST-16MI+ PCI, 16xE1/T1/J1

20128: PIST-16MI-Basic-32 PCI, 16xE1/T1/J1

20129: PIST-16MI-Basic-64 PCI, 16xE1/T1/J1

20215: T-Attenuator (monitoring tapping point)

20210/20211: Impedance Converter (75-120ohm)



CONTACT INFORMATION

Utel Systems

Televeien 9
4879 Grimstad
Norway

Tel: +47 37046192
Fax: +47 37046191

Email:
sales@utelsystems.com

Website:
<http://www.utelsystems.com/>

Updated 06.12.2006